

SP-1030 Touch Terminal







SP-1030 Touch Terminal Brings Power into POS Design & Efficiency

- Powerful 2.5GHz to 3.3GHz dual core processor
- DDR 3 memory supports up to 16GB
- Flexible modular design and dual display supports digital signage
- Convenient wall mount and wide tilt angle
- Splash and dust resistant front bezel, IP66
- Bezel Zero
- Power USB 12V*1, 24V*1(option)

Partner Tech provides the right equipment for business to expand and grow.

The SP-1030 from Partner Tech is a high performance smart POS system designed to meet the needs of today' power hungry POS and customer service applications. The choice from Celeron 2.5GHz dual-core i3 3.3GHz to i5 3.0GHz and up to 16GB of RAM, are combined in an elegant touch screen unit that features some of the most advanced and cost effective features found on any POS system.

Item	SP-1030-25	SP-1030-33	SP-1030-30
CPU	Celeron G540 2.5GHz	Ivy Bridge i3-3220 3.3	Ivy Bridge i5-3550S 3.0
	dual core	GHz dual core	GHz (up to 3.7 GHz)
			Quad core
LCD	15" Active TFT color LCD, resolution 1024 x 768, LED backlight		
Touch	5-wire Resistive touch(PS2 interface) Bezel Free/ PCT (optional)		
Memory	204pin DDR3 SO-DIMM 2GB, Maximum 16 GB		
Ethernet	IEEE 802.3 10/100/1000 BASE-T Gigabit Ethernet		
Storage	Internal 2.5" type SATA HDD x 1, Second HDD (option)		
External I/O Interface	4 * COM ports [COM1	4 on rear I/O (COM1~2 powered with	
	DC+0/5/12V, BIOS selection; COM3~4 powered with DC+0/5/12V		
	Jumper selection)		
	1 * DB-15 VGA port		
1 * RJ11 port supports 2 cash drawer			")
	1 * RJ-45 LAN port with activity and link LEDs 1 * DC+12V out 4 * USB 2.0		
	2 * USB 3.0		
	1 * DC +12V input power-jack		
	2 * Audio (1 * Line-out 1* MIC-in) or		
	Power USB 12V x1, 24V x1 (Factory Option)		
Expansion Options	1 * Mini PCI-e, Support Wireless LAN module		
Peripherals	3 tracks magnetic reader		
	Customer display module (2 x 20 VFD) or 7" LCD Monitor		
	Biometric, RFID, i-Button, IC Card reader, KB-32		
	2nd 11.6" monitor(Dual screen) /15" monitor		
Operation System	POS Ready 2009, POS Ready7, Windows XP, Windows 7,		
	Windows 8.1 Industry Pro Retail, Linux (Ubuntu)		
Power Supply	AC100~240V/DC12V15A 180 watt power adaptor		
Physical Dimensions	Physical:360mm(W)x240mm(D)x365mm(H),(LCD 15 tilt angle)		
Operating Temp	0°C ~ +40°C		
Storage Temperature	-20°C ~ +60°C		
Humidity	15%~80%		
Certification	CE, FCC, LVD, VCCI, BSMI, 3C		

* specification subject to change without prior notice

Flexible Modular Design and Dual Display Support



A wide variety of modules can be connected for different applications including RFID reader, MSR, fingerprint reader, IC card reader, and mini-PCI-E slot.

Powerful Processor



Utilizing high-power CPU the system has the power necessary to support processor intensive applications and operating systems.

Convenient Wall Mount and Wide Tilt Angle



A compact form ensures that the SP-1030 uses the minimum counter space. It's wide tilt angle (0-90 degrees) and industry standard VESA mount offers highly flexible mounting options.

Dual Cash Drawer Support



The SP-1030 supports dual cash drawers. This feature allows two cashiers to share one POS terminal for low total cost of ownership, while maintaining dedicated cash drawers for loss control.

Engineered for Reliability



The hard-drive is specialty mounted away from the touch screen protecting it from vibration. For further reliability unit can be configured with a SSD.



CARE . TRUST . RESPONSIBILITY

Partner Tech Corporation

TEL:+886-2-29188500 Taiwan FAX:+886-2-29153405 E-mail:sales@partner.com.tw USA TEL:+1-949-598-1888 FAX:+1-949-598-0088 E-mail:sales@partnertechcorp.com Europe TEL:+49 (0)40 450 635-0 FAX:+49 (0)40 450 635-130 E-mail:info@partner-tech.eu UK TEL:+44 (0)1928 579 707 FAX:+44 (0)1928 571 308 E-mail:sales@partnertechuk.com China TFI:+86-21-67696667 FAX:+86-21-67696699 E-mail:sales@partnertech.com.cn TEL:+82-2-867-8477 FAX:+82-2-867-8478 Korea E-mail:adams_c@partnertech.com.cn





