

All-in-one Touch POS Terminal



EC-1519-i3

Features

- Bezel free design
- Low speed mute fan heat treatment system
- Detachable hard disk installation
- Convenient unification of the operating system installation
- Optimize arrangement of connecting wire
- The obverse side waterproof and dustproof IP6/5
- Selectable and upgrade able Ports



Specifications

Terminal type
CPU
Main Board
BIOS
Storage
RAM Support
Network Support

Options

I/O Interface

Touch Panel
Resolution
Luminance
Viewing Angle
Storage Temperature
Operating Temperature

Dimensions
Package: carton box with Foam packaging
Mounting (Standard)
EMC/ Product Safety

15" All In One Touch POS terminal
4th Generation Intel® Core™ i3 Processors (3M Cache, 1.70 GHz or UP)
ITX- Intel Sharkbay
AMI BIOS
SSD 64G (up to 64G, 128G) / HDD (320G, up to 500G)
DDRIII 4GB up to 8GB
Realtek 8111E Gigabit Ethernet

Support ISO Trick 1/2/3 Magnetic Stripe Reader
Customer Display: VFD / Second Screen (9.7", 12", 15")
Wireless ; BT

1 * DC IN (2.5)
1 * HDMI
1 * POWER BUTTON
2 * COM (DB9)
1 * LAN
2 * USB 3.0
4 * USB 2.0
1 * LINE
1 * MIC
1 * Power LED

Flat plane five line resistance screen
XGA 1024x768 @ 60Hz
450cd / m²
left/right/up/down (+80° ~ -80° / +70° ~ -70°)
-20°C ~ 60°C
0°C ~ 40°C

460mm (W) x 410mm (D) x 250mm (H)
NW: 6.1KG ; GW: 7.0KG
VESA Compliant (100 mm x 100 mm)
FCC Class A / CE Mark / LVD / CCC

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx