

EC Thermal Receipt Printer



EC-PM-5890X

Features

- Command protocol is based on ECS / POS Standard
- Low-noise thermal printing
- Repeated operation and compy printing are possible
- Character font size (12*24 font & 24*24 font) optional
- Built-in interface provides control capabilit for cash drawer



Specifications

Dimensions (inch)	5.51" (W) x 8.85" (D) x 5.31" (H)
Dimensions (mm)	140 (W) x 225 (D) x 135 (H)
Color	Black
Weight	N.W.: 0.90 KGS / G.W.:180 KGS
Print Type	Thermal line printing
Print Direction	-
Print Resolution	Font A. 12*24 dots / Font B. 9*17 dots
Simplify / Traditional.	24*24 dots
Max Printing Speed	90 (mm) / sec
Max Printing Width	58 (mm)
Paper Thickness	0.08 (mm)
Auto Cutter	Full / Partial
Driver	Win 9X / Win ME / Win 2000 / Win NT, compatible with EPSON, SAMSUNG
Print Character / Font	ANK Character
I/O interface	Ethernet / Parallel / Serial / USB
Kitchen Print	-
Wall Mount	-
Operating Temperature	0°C -- 45 °C
Power Supply	DC 12V / 1A
Reliability Print	100Km