

EC Thermal Receipt Printer



EC-PM-80330

Features

- Fast 300 mm/s printing speed
- ESC/POS & START command sets compatible
- Interface: serial +USB+100M Ethernet standard, Parallel+USB optional
- 100M network interface card make connection and print more faster
- Support 2D barcode printing
- Standard simplified / traditional Chinese characters library
- Built-in large data buffer
- Support network printing status monitoring, computer multiple connection
- Windows driver, Linux driver, OPOS driver available



Specifications

Print method
Print width
Dot density
Print speed
Interface
Paper diameter
Line space

Character Size

Code page

Barcode mode

Fonts
BufferData
NV Flash
PowerCashdrawer out
Power supply
Weight
Dimension
Work environment
Storage environment
Reliability- Mechanism
Reliability-Auto Cutter
MTBF

Direct thermal line
Max. 72mm
512/576dot/line
300mm/s
Serial+USB+Ethernet, USB+Parallel
83mm
3.75mm(can be adjustable)

ANK Font Font A: 12x24dots Font B: 9x17dots
Simplified/Traditional Chinese Character: 24x24dots

PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/
Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/
PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/
1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/
(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)

UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/
CODABAR/CODE93/CODE128/QRCODE/PDF417

GB18030
128K bytes
256K bytes
DC 24V/1A
AC 110V/220V, 50 ~ 60Hz, DC 24V/2A
1.23kg
180x139x127mm
Temperature:0 ~ 44°C, Humidity:10 ~ 80%
Temperature:-10 ~ 60°C, Humidity:10 ~ 90%
>150km
1.5 Million Cuts
360,000 Hours

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx