

EC Thermal Receipt Printer



EC-PM-80340

Features

- Fast 300 mm/s printing speed
- Built-in speaker
- Front paper exit with auto cutter
- Support receipt detection and alarm function
- Built-in large data buffer
- Support Internet Explorer Browser and cross network setting



Specifications

Print method
Resolution
Print width
Dot density
Print speed
Interface
Paper diameter
Line space

Direct thermal line
203dpi
64/76 mm
512/576 dot/line
300mm/s
Serial+USB+Ethernet ; USB+BT ; USB+Wireless
83mm
3.75mm (can be adjusted)

Character Size

ANK Font Font A: 12×24dots Font B: 9×17dots
Simplified/Traditional Chinese Character: 24×24dots

Code page

95 alphanumeric ,48 international, 128 x 11 graphs PC437/Katakana/PC850/PC860(Portuguese)/PC863/ PC865/ West Europe/Greek / Hebrew/East Europe/ Iran/ WPC1252(ISO 8859/2/7/15) / PC866/PC852/PC858/IranII/PC851/ PC853/Page 255 /Latvian/Arabic/PT151,1251/PC737/WPC1257/Thai Vietnam/PC862/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)/(PC3847 ABNT)/(PC3848 ABICOMP) and more

Barcode mode

UPC-A/UPC-E/ JAN13(EAN13)/JAN8(EAN8)CODE39/ITF
CODABAR/CODE93/CODE128/ GS1/QRCODE/PDF417

Fonts
Buffer Data
NV Flash
Power Cashdrawer out
Power Supply
Weight
Dimension
Work environment
Storage environment
Reliability- Mechanism
Reliability-Auto Cutter
MTBF

GB18030
128K bytes
256K bytes
DC 24V/1A
AC 110V/220V, 50 ~ 60Hz, DC 24V/2A
1.35kg
197×136×141mm
Temperature:0 ~ 45°C, Humidity:10 ~ 80%
Temperature:-10 ~ 60°C, Humidity:10 ~ 90%
>150km
1.5 Million Cuts
360,000 Hours

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P.64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx