

All-in-one POS Terminal



EC-1553

Features

- CPU 1037U, 1.80 GHz
- Powered with Elo resistive touch screen
- Grade A industrial grade LCD monitor
- Wall mount Vesa mounting
- IP 65; waterproof / dust proof / oil proof
- Various interfaces combination
- Fan less Al metal construction
- 2-GB memory

Specifications

CPU
Memory
Storage
Operation System
Options

I/O Interface

Touch Panel
Viewing Area
Resolution
Active Display Area (mm)
Display Color
Response Time
Contrast Ratio
Viewing Angle
Luminance
Video Input (VGA Signal)
Input
Output
Storage Temperature
Operating Temperature
Operating Humidity
Dimensions
Mounting (Standard)
Optional (Glass)

Intel® Celeron 1037U 1.80 GHz (2MB Cache), Fanless
DDR3 SO-DIMM 2GB (2 DIMM Socket up to 16 GB)
Internal 2.5" SATA HDD x 1; [320G HDD]
Windows 7, Windows XP, XPe, Linux (Ubuntu, Fedora) , WEPOS, POS Ready
Support wireless LAN mode / 3 tracks magnetic reader
Customer display module (2*20 VFD) / 10.4" LCD 2nd display module
4 * COM ports [COM1~4 at back I/O (Powered with DC+0/5/12V, COM1~2 by BIOS Selection; COM 3~4 by jumper setting)]
1 * DB-15 VGA port
1 * DB-25 for LPT port
1 * RJ11 port for 2 cash drawer (+24V)
1 * RJ-45 LAN port with activity and link LEDs
1 * PS/2 KB
4 * USB 2.0 (4 in the back, One for Mini-PCI-e,
One for MSR+RFID reader, Two Reserved)
1 * DC +12V power adaptor connector
5-wire resistive (PS2 interface)
15 inches
1024 x 768
304.128 (W) x 228.96 (H)
16,777,216 colors
8 ms
600 : 1
(Up/ Down/ Left/ R 70°/ 60°/ 75°/ 75°
250 cd/m
LVDS
Universal AC 100 - 240 V
DC + 12 V, 90 W power adaptor
-20°C -- 60°C
0°C -- 40°C
15 % -- 80 %
360mm (W) x 233mm (D) x 323mm (H)
VESA Compliant (100 mm x 100 mm)
Strengthen Glass (for none-touch version)



Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx