

All-in-one POS Terminal



EC-1200

Features

- Power with EETI resistive touch screen
- Grade A industrial grade LCD monitor
- Wall mount VESA mounting
- Various interfaces combination
- Fanless Al metal construction
- Optional second display and VFD



Specifications

CPU
Memory
Storage
LAN
Operation System
Optional Peripherals

I/O Interface

Viewing Area
Resolution
Active Display Area (mm)
Display Color
Response Time
Contrast Ratio
Viewing Angle
Touch Panel
Luminance
Video Input (VGA Signal)
Input
Output

Management
Consumption
Storage Temperature
Operating Temperature
Operating Humidity
Rotation (Vertical)
Mounting (Standard)
Optional (Glass)

Intel D525 + ICH8 chipset
DDRIII 1066 / 1333*1 2GB (up to 4GB)
32GB SSD / Optional 64GB / 128GB SSD
10/100/1000 Mbps gigabit ethernet
Windows 7, Windows XP, XPe, Linux (Ubuntu, Fedora), WEPOS, POSReady
3 tracks magnetic reader
Customer display modules
10.4" LCD 2nd display module
3 * COM ports (COM1~3 at back I/O)
1 * DB-15 VGA port
1 * DB-25 for LPT port
1 * RJ11 port for 2 cash drawer (+24V)
1 * RJ-45 LAN port with activity and link LEDs
1 * Audio ports (1 * line-out, 1 * MIC-in)
4 * USB 2.0 (4 in the back, One for Mini-PCI-e)

12 inches
800 x 600 or 1024 x 768 (max)
304.128 (W) x 228.96 (H)
16,777,216 colors
8 ms
600 : 1
(Up/ Down/ Left/ R 70°/ 60°/ 75°/ 75°
4-wire resistive
250 cd/m
LVDS
Universal AC 100 - 240 V
DC + 12 V

VESA DPMS
40W
-20°C -- 60°C
0°C -- 40°C
10 % -- 85 %
90°
VESA Compliant (100 mm x 100 mm)
Strengthen Glass (for none-touch version)

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx