

Multi Language Customer Display



EC-VFD-3010

Features

- Vacuum Fluorescent Display
- 2 x 20 characters
- Supports 14 languages
- Compatible with 6 command sets
- Innovative hinge design enables easy angle adjustment
- Display adjustable range : 0-270° horizontally, 0-36° vertically
- Bluetooth module optional

Specifications

Display Type
Font Size
White luminance (Center)
Interface
Command Set

Vacuum fluorescent Display
5 x 7 Dots
700 cd/m²
USB/ RS233
EPSON ESC/POS
ADM787/788
EMAX (AEDEX)
UTC/S, UTC/P
CD5220
DSP-800 (option)

Character Type

- 96 alphanumeric characters
- 14 sets of international characters: USA, France, Germany, UK, Sweden, Denmark I and II, Italy, Spain, Norway, Japan (Katakana), Slavonic, Russian and Portuguese
- One set of user downloadable characters

Chassis Color
Power Supply
Power Consumption

Black
DC 7V~36V
3~5W

Operating Temperature
Storage Temperature
Operating Humidity
Storage Humidity
MTBF
Certification
Head Dimension
Support Dimension
Base Dimension

5°C - 40°C
-20°C ~ 70°C
Max. 80%
Max. 90%
25,000 hrs
CE/FCC
215 (W) x 57 (D) x 92 (H) mm
Long : 250 (H) x 34 (Ø) mm ; Short : 117 (H) x 34 (Ø) mm
200 (W) x 120 (D) x 27 (H) mm



Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx