

Label Pinter



EC-Q8-PLUS

Features

- 3inch print width
- 6inch / sec ultra high print speed
- Support 2D barcode printing
- Label paper auto positioned
- Compatible with various label software
- BMP, PCX, BAS files download and storage supported
- Support print media en 16mm to 82mm range, easy operation design
- Paper auto checkout and temperature auto controlled function
- Compatible with variuos label software



Specifications

Printing Method
Printing Resolution
Max Printing Speed
Max Printing Width
Max Printing Length
Memory

Direct Thermal & Thermal Transfer
203 dpi (8 dots/mm)
4 ips (101.6 mm/s)
4.25" (108 mm)
1.57" (4000 mm)
32-bit ARM Processor, 2 MB FLASH ROM, 8 MB SDRAM

Media

Roll-feed, die-cut, continuous, tags, tickets in plain paper or thermal paper
Width: 110 mm max., 25 mm min.
Supply roll: OD 5" (127 mm) max., ID 1" (25.4 mm) min.
Thickness: 0.003" - 0.006" (0.08" - 0.15 mm), including liner
Wax, Wax/Resin, Resin
Ribbon roll: OD 1.5" (38 mm) max., ID 0.5" (12.7 mm) core
Max width: 110 mm; Max length: 110 M. Ink side: Out
Five built-in ASCII fonts; Optional multiple language fonts

Ribbon

Fonts

Bar code Types

1D Barcode: eode 39, eode 93, eode 128/subset A,B,e, eodabar,
Interleave 2 of 5, UPeA/E 2 and 5 add-on, EAN-13/8/128, uee-128
2D Barcode: Maxieode, PDF417, Data Matrix, QR

Media sensor
Interfaces
Power rating
Weight

Reflective (multiple mounting positions)
RS-232 serial, USB
24 VDe Power adapter
4.621bs (2.1 kgs)

Dimensions

W 8.27" x D 10.04" x H 5.9" (W 210 x D 255 x H 150 mm)

Operation
Environment

Temperature: 32° F - +104° F (0° e - 40° e)
Relative humidity: So/o - 85% non condensing

Storage Environment

Temperature: -40° F - +140° F (-40° e - 60° e)
Relative humidity: So/o - 85% non condensing

Optional Items

Guillotine cutter, Peeler Kit, External Rewinder

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx