

EC Dot Matrix Printer



EC-PM-530B

Features

- ESC/POS & START command sets compatible
- With Auto Cutter
- Interface: Ethernet+USB / Parallel / Serial+USB / Bluetooth / WiFi
- Standard simplified / traditional Chinese characters library
- Built-in large data buffer
- Windows driver, Linux driver, OPOS driver available



Specifications

Print method
Print Resolution
Max Printing Width
Paper Thickness Support

Print speed
Interface

Driver

Kitchen Print

Character Size

Fonts

Power supply
Power Adaptor Input
Power Adaptor Output

Weight
Dimension
Work environment

Reliability- Mechanism
Reliability-Auto Cutter

9-pin impact dot matrix
160 x 144 dpi (Max)
Max.63.4 mm

- Single sheet roll paper: 0.06 - 0.085 mm
- Two-sheet, trilogy copy paper (each page): 0.05 ~ 0.08 mm
- total thickness $\leq$ 0.14 mm
- Max.4.7 LPS (40 columns,16 cpi)
- Ethernet+USB / Parallel / Serial+USB / Bluetooth / WiFi

Win 9X / Win ME / Win 2000 / Win 2003
/ Wint NT/ Win XP/ Win Vista,
compatible with EPSON
Support

ASCII sets, International character sets;
Big 5 15x16 character (for HK and Taiwan version)
GB18030

DC 24V/2.5A
AC100V ~ 240V, 50~60HZ

2.9kg
162 W x 253 D x 140 H (mm)
Temperature:5~ 35°C, Humidity:25 ~ 80%

150km
Ceramic Auto-cutter with life: 1.5 million times

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx