

EM Card Reader



EC-C202D

Features

- Complies with ISO 7812, IBM standards
- Supports multi-country code settings
- Supports programmable MSR setting
- Available for USB (HID), KB Wedge and RS232



Specifications

Operating Voltage
Power Consumption
Scan Rate
Track Information

DC 5V $\pm$ 5%
80 mA
100 ~1000mm per second
Single track (1st, 2nd, 3rd Track)
Dual tracks (1&2 , 2&3 Tracks)
Tripe tracks (1&2&3 Tracks)
JIS II

Interface
Connector

KBW / RS232 / USB / TTL
JAE 10P Pitch 2.0

Life Cycle

500,000 passes

Dimension (mm)
Weight (g)

135 (mm) x 47 (mm) x 45 (mm)
220g

Read / Write

Read (High / Low coercive)

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx