



SURPASS SERIES - Desktop Direct Thermal Label Printer

4" Wide EC-GS-2408D

POWERFUL, HIGH PERFORMANCE, AFFORDABLE



KEY FEATURES

- 203.2mm (8") per second print speed for 203 DPI.
- 400 MHz 32-bit ARM9 processor with 64 MB SDRAM, 32 MB Flash memory or 64 MB SDRAM, 128 MB Flash memory.
- Internally scalable true type font engine.
- USB Host for scanner or PC keyboard.
- Firmware emulates EPL, ZPL, ZPL II, DPL, TSPL.
- BarTender Free Windows® drivers and label design software (available via download).
- Provide Windows printer utility, Windows SDK and Android SDK.
- Solution for retail POS, shelf labeling, office application, shipping.

SURPASS SERIES -

4" Desktop Direct Thermal Label Printer



PRINTER MODEL	GS-2408DE	GS-3405DE	GS-2408DM	GS-3405DM
Level	Economic	Economic	Empower	Empower
Resolution	8dots/mm (203DPI)	12dots/mm (300DPI)	8dots/mm (203DPI)	12dots/mm (300DPI)
Printing Method	Direct Thermal			
Max. print speed	203.2mm (8'')/second	127mm (5'')/second	203.2mm (8'')/second	127mm (5'')/second
Max. print width	104mm (4.1'')	108.4mm (4.27'')	104mm (4.1'')	108.4mm (4.27'')
Max. print length	2,794mm (110'')	1,016mm (40'')	25,400mm (1000'')	11,430mm (450'')
CPU	400MHZ, 32-bits, ARM9			
Memory RAM	64MB SDRAM		64MB SDRAM	
Memory ROM	32MB Flash Memory		128MB Flash Memory	
Interface	USB 2.0 High Speed 480Mbps USB Host 2.0, for scanner or PC keyboard Internal Ethernet 10/100Mbps		USB 2.0 High Speed 480Mbps USB Host 2.0, for scanner or PC keyboard Internal Ethernet 10/100Mbps Internal Bluetooth 4.0 (factory option) Internal Wi-Fi (factory option)	
Real Time Clock	N/A		Standard (CR2032 Battery Install)	
Buzzer	N/A		Standard	
Dealer options	N/A		Guillotine cutter (full cut and partial cut)	
Sensors	Head open sensor, Reflective sensor (moveable), Transmissive sensor (moveable)			
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz, Output: DC 24V, 2.5A, 60W			
User Interface	1 power switch, 2 buttons (Feed & Pause), 2 LEDs (Online, Error)			
Internal fonts	8 alpha-numeric bitmap fonts True type font engine (need download scalable font file)			
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Plessey, PostCode, Telepen			
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix			
Rotation	Font and barcode support 0, 90, 180, 270 degree			
Printer language	Compatible to EPL, ZPL, ZPL II, DPL, TSPL			
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)			
Media width	15~112mm (0.6''~4.4'')			
Media thickness	0.055~0.254mm (2.17~10mil)			
Media core diameter	25.4mm (1'')			
Label roll capacity	127mm (5'')OD			
Label length	5~2,794mm (0.2''~110'')	5~1,016mm (0.2''~40'')	5~25,400mm (0.2''~1000'')	5~11,430mm (0.2''~450'')
Physical dimension	176mmx180mmx240mm (WHD)			
Weight	1.76kg		1.8kg	

Enclosure

ABS plastic

Certification

FCC, CE, CCC, BIS, CB

Environment condition

Operation: 5~40°C, 25~85% non-condensing
Storage: -40~60°C, 10~90% non-condensing

Environment concern

Comply with RoHS, REACH, WEEE

Accessories

Windows labeling software CD disk/Quick start guide/USB cable/Power cord External universal switching power supply

Limited warranty

Printer: 2 years
Print head: 25km (1 million inches)/12 months
Roller: 50km (2 million inches)/12 months

User options

External roll mount