

Magstripe & Programmable Keyboard



EC-K78



Features

- 78 Cherry MX keys based on Gold Crosspoint technology
- Two different key actions (soft contact and keyclick)
- Different relegendable keycaps
- Comply with ISO 7812, IBM standards, American Driving License

Specifications

Power supply

PS/2: +5V/DC $\pm 10\%$; $<100\text{mA}$
USB: +5V/DC $\pm 5\%$; $<100\text{mA}$

Soft contact mode
Key click mode

50 million strokes
20 million strokes

Total travel
Pre-travel
Peak load before make
Lifecycle

4 – 0.4mm
 $2 \pm 0.6\text{mm}$
 $60 \pm 20\text{cN}$
 $\geq 25,000$ times

Storage temperature
Operating temperature
Operating humidity
Dimension (LxWxH, mm)

-40°C to $+60^{\circ}\text{C}$
 0°C to $+50^{\circ}\text{C}$
20% to 90%
290 x 175 x 52

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx