

Touch Screen Monitor



EC-TS-1510-USB

Features

- LIYITEC/ Wan da five-wire resistive technology
- Drip-proof enclosure, touchscreen sealed
- Touch can be activated with gloved hands
- Multiple mounting options including VESA
- Built in speakers (optional)
- On screen display controls on the side



Specifications

Panel size	15.0 inch
Aspect Ratio	4:3 (W:H)
Display area	304.128(W)×228.096(H) mm
View Angle	Horizon : 140 ; Vertical : 125
Display color	16.2M
Resolution	XGA 1024*768 @ 75Hz
Brightness	350cd/m (Typ)
Contrast Ratio	700:1
Touch screen	5 wire Resistive touch screen
Response time	6ms
Signal interface	LVDS(1ch,8-bit)
Touch interface	USB
Operating Temperature	0 °C to 40°C
Storage Humidity	20%~80%
Storage Temperature	-20°C to 60°C
Rear I/O ports	Analog: 15-pin-D-SUB, USB touch input, DC 12V input , Audio : line in (optional)
Power adaptor	100-250V/50-60HZ AC power input , DC 12V/3A output
Power Consumption	25W(max)
EMI/ Product Safety	TUV,CE,VCCI,FCC
Packing dimension	460*420*240 (mm)
Package: carton box with Foam packaging	NW:6.3KG GW:7.3KG

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P.64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx