

All-in-one POS Terminal



EC-VP-1100 J6412

Features

- All-in-one FANLESS POS System
- 15" Bezel free with Capacitive touch
- Flexible architectures for peripheral
MSR / VFD / 15" Second display supported
- Hidden cable management for space management

Specifications

Processor
Memory
Storage

Intel® J6412 Quad Core up to 2.60GHz
DDR4 4G DDR4-2666/2933MHz, Up to 16GB
128 / 256GB SSD or
500GB SATA HDD

OS Supported

Windows 10 / 10 IOT, Windows 11, Linux (ubuntu)

Display Size
Touch
Resolution
Brightness
Contrast Ratio
Response Time
Viewing Angle
Video Interface

15 Inches
10-point Projected Capacitive Touch
1024 × 768
350cd /m²
600:1
10ms
80°/80°/70°/70° (Up/ Down/ Left/ Right)
EDP

I/O Interface

DC12V IN / DC12V OUT
1 × HDMI
2 × USB2.0
4 × USB3.0
2 × RS232
1 × CASH DRAWER(RJ11)

Power

Input: AC 100-240V
Output: DC 12V/5A
-10°C ~ 50°C (14°F ~ 122°F)
15 % ~ 85 %
350 × 220 × 340 mm, N.W. 4.9 Kg
440 × 310 × 413 mm, G.W. 6.8 Kg

Operating Temperature
Operating Humidity
Dimensions (W x D x H)
Packing Dimensions (W x D x H)

FCC / CE / RoHS
ISO Trick 1/2/3 Magnetic Stripe Reader
VFD / Second Display (10.1", 15")
Wireless / iButton / Finger Sensor

Safety
Optional Peripherals



With 15" Second Display



With 15" A-shape Second Display

*All rights reserved. All specifications are subject to change without notice. 保留隨時更改本文中產品相關描述之權利。若有更改恕不另行通知。

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx