

All-in-one POS Terminal



EC-VP-1100i3/i5-4th

Features

- All-in-one FANLESS POS System
- 15" Bezel free with Capacitive touch
- Flexible architectures for peripheral
MSR / VFD / 10.1"/15" Second display supported
- Hidden cable management for space management

Specifications

Processor

Intel® Processor I3 4120 Dual-core 2.0G
Intel® Processor I5 4300 Dual-core 1.9G
DDRIII-1600 4GB (up to 8GB)
60GB SSD

Memory Storage

OS Supported

Windows 7, Windows 8.1, Windows Embedded 8.1 Industry
Windows 10

Display Size

Touch
Resolution
Brightness
Contrast Ratio
Response Time
Viewing Angle (Up/ Down/ Left/ Right)
Video Interface

15 Inches
10-point Projected Capacitive Touch
1024 x 768
350cd /m²
600:1
10ms
80°/80°/70°/70°
LVDS

I/O Interface

DC12V IN / DC12V OUT
1 x VGA
1 x HDMI
2 x USB2.0
2 x USB3.0
1 x LAN
3 x COM(DB9)
1 x CASH DRAWER(RJ11)

Power

Storage Temperature
Operating Temperature
Operating Humidity
Dimensions (W x D x H)
Packing Dimensions (W x D x H)

Input: AC 100-240V
Output: DC 12V/5A
-20°C to 60°C
-10°C ~ 50°C (14°F ~ 122°F)
15% ~ 85%
350 x 220 x 340 mm, N.W. 4.9 Kg
440 x 310 x 413 mm, G.W. 6.8 Kg

Safety
IP Rating
Optional Peripherals

FCC / CE / RoHS
IP54
ISO Trick 1/2/3 Magnetic Stripe Reader
VFD / Second Display (10.1", 15")
Wireless / iButton



With 15" Second Display



With 15" A-shape Second Display

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx