

All-in-one POS Terminal



EC-VP-3100

Features

- All-in-one FANLESS POS System
- 15.6" Bezel free with Capacitive touch
- Flexible architectures for peripheral
MSR / VFD / 10.1" / 15.6" Second display supported
- Hidden cable management for space management

Specifications

Processor

Intel® Celeron® Processor J1900 2.4GHz
Intel® Core i3-7020U Processor 2.3GHz
Intel® Core i5-6360U Processor 3.1GHz
DDRIII-1600 4GB (up to 8GB)
128GB SSD (up to 256GB)
Dual Storage (1 × Removable + 1 × Fixed)

System Memory Storage

OS Supported

Windows 7, Windows 8.1, Windows Embedded 8.1 Industry,
Windows 10 Home / Pro, Windows 10 IOT, POS Ready 7

Display Size Touch Panel Display Ratio Resolution Brightness Contrast Ratio Response Time Viewing Angle (Up/ Down/ Left/ Right) Video Interface

15.6 Inches
10-point Projected Capacitive Touch
16 : 9
1366 × 768 (Default) / 1024 × 768
220cd/m²
600:1
10ms

I/O Interface

IPS
LVDS
DC12V IN / DC12V OUT
1 × VGA
3 × USB2.0 (I3/I5: 2 × USB2.0)
1 × USB3.0 (I3/I5: 2 × USB3.0)
1 × LAN
3 × COM (DB9)
1 × CASH DRAWER (RJ11)

Power

Operating Temperature Operating Humidity Dimensions (W x D x H) Packing Dimensions (W x D x H) VESA Mounting Safety Optional Peripherals

Input: AC 100-240V
Output: DC 12V/5A
-10°C ~ 50°C (14°F ~ 122°F)
15% ~ 85%
387 × 200 × 315 mm, N.W. 4.9 Kg
440 × 310 × 413 mm, G.W. 6.8 Kg
75 × 75 (mm) & 100 × 100 (mm)
FCC / CE / RoHS
ISO Track 1/2/3 Magnetic Stripe Reader
2×20 VFD / 10.1" Second Display
iButton / Fingerprint



*All rights reserved. All specifications are subject to change without notice. 保留隨時更改本文中產品相關描述之權利。若有更改恕不另行通知。

Asia, Pacific: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx