

Wall Mount Digital Signage

Professional LCD Display



EC i-Connect
True value in Signage

***EC-WDS32I / EC-WDS43I /
EC-WDS49I / EC-WDS55I /
EC-WDS65I***



*All rights reserved. All specifications are subject to change without notice. 保留隨時更改本文中產品相關描述之權利，若有更改恕不另行通知。

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

Wall Mount Digital Signage



Specifications

MODEL	EC-WDS32I	EC-WDS43I	EC-WDS49I	EC-WDS55I	EC-WDS65I
LCD PANEL					
Panel Size	32 inch	43 inch	49 inch	55 inch	65 inch
Display Area (H x V)(mm)	700.4 x 394.8	943 x 531.5	1075.8 x 606	1211.6 x 682.5	1430.5 x 805.3
Display Mode	16:9				
LCD Type	LG - IPS				
Resolution	1920 x 1080	3840 x 2160 (4K UHD)			
Brightness	500 cd/m²				
Response Time	8 ms				
Color System	PAL / NTSC / Auto				
Field Frequency	60 Hz				
Contrast Ratio	1000 : 1	1400 : 1			
View- angle (up/down/left/right)	89° / 89° / 89° / 89°				
MEDIA FORMAT					
System	Android Operating System				
Royal TS	B/S TS				
Media Format	avi / flv / mkv / mp4 / mpeg / rm / rmvb / ts / wmv				
Text Format	doc / docx / pdf / ppt / pptx / txt / xls / xlsx				
Picture Format	bmp / gif / jpeg / jpg / png				
SYSTEM					
CPU	Quad-core ARM Cortex A17	Quad-core ARM Cortex A53			
DDR	DDR3 2GB	DDR4 2GB			
Internal Memory	EMMC 8GB (4GB Available)				
Wireless	Onboard · 802.11b/g/n				
INTERFACE					
HDMI	N/A	HDMI IN x 1			
Ethernet	RJ45 10M/100M Ethernet x 1				
USB	USB2.0 x 2				
POWER					
Power Requirement	AC100V ~ 240V · 50/60Hz				
Power Consumption – Typical	≤80W	≤80W	≤110W	≤130W	≤140W
Power Consumption – Standby	< 1W				
PHYSICAL SPECIFICATIONS					
Frame Material	Aluminum + Metal Back Cover + Tempered Glass Panel				
Dimensions – without Wall Mount Kit (W x H x D) (mm)	751.8 x 446.2 x 53	994.6 x 582.9 x 52.6	1127.2 x 657.4 x 52.6	1263 x 733.8 x 52.6	1482 x 857 x 52.6
Net Weight (KG)	12.5	21	25	30	38
ENVIRONMENTAL CONDITIONS					
Operating Temperature	0°C~50°C				
Storage Temperature	-20°C~60°C				
ACCESSORIES					
Included	Power cord / Standard Wall Mount Kit				

*All rights reserved. All specifications are subject to change without notice. 保留隨時更改本文中產品相關描述之權利，若有更改恕不另行通知。
Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk