


Rugged i9000S Smart POS Payment Terminal

27TW



Multiple Payment Solutions

MSR, Chip card, NFC
2D payment
Membership rewards point

Powerful Data Collection

Optional 1D or 2D scan engine
5MP camera
GPS positioning

Advance capacitive screen

5" HD(720 × 1280)
Industrial grade sensitivity,
works with gloves and wet fingers.

Optional module

Thermal Printer

2 inch thermal printer
30mm paper roll
Supports 2D barcode printing



Finger print
(4000mAh battery)



Rugged i9000S Smart POS Payment Terminal

Basic Characteristics

| | |
|-----------------|--|
| O.S. | Safedroid OS (based on Android 8.1), supports multi-language |
| CPU | Quad-Core 1.2GHz |
| Display | 5.0 inch TFT-LCD HD (720 x 1280) color screen |
| Panel | Ultra sensitive capacitive touch panel, can work with gloves and wet fingers |
| RAM | 2GB |
| ROM | 16GB |
| Dimensions | 184mm x 81 mm x 32mm (max 51mm) |
| Weight | 550g (Battery included) |
| Buttons | Front: User define button x 1, Cancel button x 1, Confirm button x 1, Clear button x 1 Side: SCAN button x 2, The volume switch button, ON / OFF button |
| Input | Supports handwriting and soft keyboard |
| Barcode Scanner | 1D Laser / 2D Imager |

Radio Communication

| | |
|---------------------|--|
| Wi-Fi | 802.11 b/g/n wireless communication |
| Bluetooth | Bluetooth 4.1 |
| Radio Communication | 4G TDD-LTE: B40 FDD-FTE: B1/B2/B3/B4/B5/B7/B8/B20 |
| | 3G WCDMA: B1/B2/B5/B8 |
| | 2G GSM/EDGE/GPRS/CDMA: 850/900 /1800/1900MHz |

Power

| | |
|--------------|---|
| Main Battery | Rechargeable 3.8V, 5000mAh lithium polymer battery pack (Typical Operation time ≥8 hours) |
| RTC Battery | Real time clock battery |

Payment

| | |
|-------------------------|--|
| Magcard | Supports ISO7811/7812/7813, and supports triple track (tracks 1/ 2/ 3), bi-directional |
| Chip Card | Supports ISO7816 standard |
| Contactless Cards(RFID) | Supports 15693; Supports 14443A / 14443B; Supports 10MHz~20MHz frequency, and reading time less than 300 milliseconds |
| Printer | 58mm printing paper, 203dpi / 8dot / mm; Printing speed: 50~70mm/s, and supports barcode printing , 30mm media roll size |

Expansion and Peripherals

| | |
|------------|---|
| Camera | 5MP camera with LED flash and auto-focus function |
| GPS | GPS, Supports A-GPS, GLONASS, Beidou |
| Slot | Micro SD/TF x 1(a maximum of 32 GB), SIM x 1, SAM x 2 |
| PSAM | SAM x 2 Conforms to ISO7816 standard |
| Interfaces | Mini USB x 1, Pogo pin x 1, 3.5mm Audio Jack x 1, DC Jack |
| Audio | Microphone, Earpiece, Speaker |

Accessories

| | |
|----------|--|
| Standard | Power adaptor, USB cable, One battery. |
| Optional | Dual-Slot Battery Charger, Carrying Pouch, Cradle, Hand Strap, Stylus, Media roll. |

User Environment

| | |
|-----------------------|---------------------------|
| Operating Temperature | -10~50℃ (-14~122°F) |
| Storage Temperature | -40~70℃ (-40~158°F) |
| Humidity | 5% ~ 95% (non condensing) |
| Drop Durability | 1.2m |

Product Certification

| | |
|---------------|--|
| Certification | CCC, CE, FCC, RoHS, PCI, EMV LEVEL 1&2, EMV Contactless LEVEL 1 certification, PayWave, PayPass, American Express Expresspay |
|---------------|--|

Accessories



Hand Strap



Cradle



Dual-Slot Battery Charger